

# ABS-Lock X-H-4

Fall Protection Anchor Wood | screwed



## Anchorage point for wooden structures – designed for floor installation

Our ABS-Lock X-H-4 anchorage device is simply screwed straight onto a load-bearing beam using the 4 stainless steel screws supplied. Dimensions: The anchor rod is 16 mm in diameter; the base plate measures 100 x 100 mm. This anchorage device has been designed exclusively for lateral loads and can secure up to 3 individuals.

Upgrade your ABS-Lock X-H-4 anchor by adding an optional **supporting tube** to implement it as an end or corner component in a lifeline system. This additional tube serves to stabilize the anchorage point and to cope with the prescribed pre-tensioning load.

Combine your ABS-Lock X-H-4 with other ABS anchorage devices to create a lifeline system tailored to meet your own individual needs. Our **Team** would be happy to provide you with any help or information you may need!

- EN 795:2012, A + CEN/TS 16415:201
- Designed for load-bearing wooden structures
- Min. beam dimensions: 100 mm x 120 mm
- Installation materials included
- Add a supporting tube for usage as an end or corner post in a lifeline system



- Wood
- Flat Roofs
- DIN EN 795
- DIN EN 795
- screwed
- Three Persons
- Stainless Steel
- Lateral and Axial
- HLL Intermediate
- End and corner support